



## **LGR 3500i**

Our largest-capacity dehumidifier - control humidity in spaces up to 17,000 cubic feet. Industry-leading performance in a highly durable and portable package. Automatically adjusts operation to maximize performance in high or low humidity conditions. Features the new Command Hub touchscreen controller—see job conditions at a glance and adjust your setup to maximize drying efficiency. Displays grain depression, graphs drying progress, quick access to humidistat settings, and more.



## **FEATURES**

- NEW! Command Hub touchscreen controller displays real-time temp, RH, grain depression and drying progress trends at a glance. Controller upgrade package for existing i-Series dehumidifiers also available. Learn more.
- Fast and convenient access to humidistat, job hours, maintenance reminders and more.
- Digital control panel with plain-English system messages, not codes.
- Rugged Dri-Eaz rotomolded housing is easy to maintain and won't mar furnishings.
- Automatic restart after outage when power is restored.

## **SPECIFICATIONS**

- Water removal AHAM (80°F/60%RH): 170 pts. | 80.4 L /day
- Water removal Max. (90°F/90%RH): 240 pts. | 113.6 L /day
- Process Air: 400 CFM | 679.7 CMH
- **Dimensions (W × H × D)**: 24 × 40.5 × 23 in. | 61 × 103 × 58 cm
- Use weight: 158 lbs. | 71.2 kg

• **Amps**: 11.2A

• **Volts**: 115V

• Frequency: 60Hz

• Air filter: 4-PRO filter

• Hose: 40 ft. | 12.2 m

• Power cord: 25 ft. | 7.6 m detachable

• Housing: Rotomolded polyethylene

• Safety: ETL listed to CSA 22.2 no. 92

Xactimate: WTRDHM>>>XXL

## **SIZES - OPTIONS**

• 110133 (F411): One unit