



LGR 6000Li

Get the quietest and best-performing compact, easy-transport i-Series dehumidifier your techs will always choose first. The LGR 6000Li is perfectly sized for everyday jobs, and it's Dri-Eaz rugged, ready to withstand years of heavy use. Removes more water than any other competitive unit in its class. Features the new [Command Hub touchscreen controller](#)—see job conditions at a glance and adjust your setup to maximize drying efficiency. Displays grain depression, graphs drying progress, quick access to humidistat settings, and more.



FEATURES

- Extreme Dewpoint Technology™ (EDT) delivers the fastest response to changing conditions.
- NEW! Command Hub touchscreen controller displays real-time temp, RH, grain depression and drying progress trends at a glance. Controller upgrade package for existing i-Series dehumidifiers also available. [Learn more.](#)
- Fast and convenient access to humidistat, job hours, maintenance reminders and more.
- Process outlet fits 12 in. layflat and rigid ducting.
- Uses all-in-one 4-PRO filter: electrostatic mesh filtration with antimicrobial treatment and odor-fighting carbon.
- Easily ductable using built-in snap-ring mount on air outlet.
- Unique spill-proof pump basin keeps in any water left after the final purge cycle.
- Fast 4-bolt access for easy cleaning and preventive maintenance.
- Practically indestructible, rolls up stairs easily and stacks for storage.

SIZES ▪ OPTIONS

- **103614 (F600)**: One unit

SPECIFICATIONS

- **Water removal AHAM (80°F/60% RH)**: 100 pts. | 47.3 liters / day
- **Water removal Saturation (90°F/90% RH)**: 204 pts. | 96.5 liters / day
- **Water removal LGR (80°F/20% RH)**: 40% higher than competitive units
- **Process air (max.)**: 320 CFM
- **Dimensions (H × D × W)**: 32.1 × 19.8 × 20.0 in. | 81.5 × 50.3 × 50.8 cm
- **Weight**: 103 lbs. | 46.7 kg
- **Amps**: 6.6A
- **Volts**: 115V
- **Frequency**: 60Hz
- **Power**: 759W
- **Operating range**: 33°F–100°F | 1°C–38°C
- **Noise level (avg.)**: 53 dB
- **Drain hose**: 40 ft. | 12.2 m
- **Power cord**: 25 ft. | 7.6 m
- **Housing**: Rotomolded polyethylene
- **Air filter**: 4-PRO filter
- **Safety**: ETL listed CSA 22.2 no. 92
- **Xactimate**: WTRDHM>L