



# Velo Pro Low Profile Airmover

Unbeatable versatility and portability. Precisely control power draw from 1.2–1.9 amps and daisy-chain up to 10 units on a single 15-amp circuit. A built-in kickstand provides a total of five operating positions. Don't need variable speed control? Chose the Velo airmover.

## FEATURES

- Adjust amp draw from 1.2-1.9 amps in .1-amp increments to balance draw in limited power settings
- Variable speed control from 500 (min.) to 885 (max.) CFM.
- Daisy-chain capable with convenient dual outlet.
- Hour meter to track usage and maintenance intervals
- Patented outlet design ensures even, broad-path airflow for fast, consistent drying across all surfaces.
- Five operating positions. Dry floors, ceilings, walls and stairways quickly and efficiently.
- Great portability. Easily carry two units at once - or stack up to six on a hand truck.
- Easiest to maintain. Simply remove fasteners and lift out impeller assembly for cleaning.

## SIZES • OPTIONS

- **114969 (F505):** One unit



## SPECIFICATIONS

- **Power (115v, 60 Hz):** 1.2 - 1.9 amps
- **Air movement:** 885 CFM (max.) / 500 CFM (min.)
- **Velocity:** 1930 FPM (max.)
- **Controls:** Variable speed with on/off switch
- **Static pressure:** 1.65 in. / H2O
- **Weight:** 18.6 lbs. | 8.4 kg
- **Dimensions (W × H × D):** 18 × 8.8 × 23.6 in. | 45.7 × 22.4 × 60 cm
- **Cord length:** 18 ft. | 5.5 m
- **Watts:** 185W
- **Fan:** 6 blade impeller-type
- **Sound level:** 69 dB
- **Construction:** Injection-molded housing, steel wire inlet and outlet grills.
- **Safety:** ETL listed to UL/cUL and CSA standards
- **Xactimate:** WTRDRY